

Product Search Data Sheet

CFULB455KD1Y-B0


Note: This datasheet may be out of date. <u>Please download the latest datasheet of CFULB455KD1Y-B0 from the official website of Murata Manufacturing</u> Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=CFULB455KD1Y-B0



### Appearance & Shape







Ceramic filter CFULB\_Y series are miniature and high-performance filters. These filters, only 6.3mm high, are 65% the volume of conventional types. Well suited for miniaturizing communications equipment, especially for a cellular phone.

Features

- 1. Miniature, flat GDT characteristics
- 2. Suitable for a cellular phone
- 3. Avariety of bandwidths are available.

4. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)

### Applications

Other Usage Communication Equipment	Other Usage	Communication Equipment
-------------------------------------	-------------	-------------------------

### Packaging Information

Packaging	Specifications	Minimum Order Quantity
-B0	Bulk	250

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of CFULB455KD1Y-B0 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=CFULB455KD1Y-B0

# CFULB455KD1Y-B0

## Specifications

Operating Temperature Range	-20°C to 80°C	
Shape	Lead	
Elements	4	
Center Frequency	455.0kHz	
Center Frequency Tolerance	±1 kHz	
Nominal Center Value	No	
6dB Bandwidth	fn±10.0kHzmin.	
Stop Bandwidth	25.0kHz	
Area of Stop Bandwidth	[within 40dB]	
Stop Band Attenuation	23dB[within fn±100kHz]	
Insertion Loss	7.0dB[at minimum loss point]	
Ripple	1.0dB[within fn±7kHz]	
GDT Deviation	20.0µs[within fn±7kHz]	
Input/Output Impedance	1500Ω	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet




### CFULB455KD1Y-B0


Note: This datasheet may be out of date.

Please download the latest datasheet of CFULB455KD1Y-B0 from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=CFULB455KD1Y-B0








**Frequency Characteristics** 

Spurious Response



Rg+R1=R2=Input/Output Impedance

Measurement Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.