

Note: This datasheet may be out of date Please download the latest datasheet of LFB182G60SGHC149 from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=LFB182G60SGHC149

LFB182G60SGHC149












Appearance & Shape









Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.

Extremely ultra-small band-bass filters.

- 1. Ultra-small, low-profiled, lightweight band-pass filters.
- 2. Absolutely no adjustment required.
- 3. Reflow solderable.
- 4. Available in tape and reel packagings for automatic mounting.
- 5. Available in the 2500MHz to 2700MHz frequency range.

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Paper Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/06/22



Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ LFB182G60SGHC149 \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

1.60x0.80mm


0.65mm

L x W (size)

Thickness(max.)

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=LFB182G60SGHC149} \\$

LFB182G60SGHC149



Applications	WIMAX
Nominal Center Frequency(fo)	2600.00MHz
Bandwidth(BW)	fo±100.00MHz
Insertion Loss in BW I)	2.2dB max. (at 25°C)
Insertion Loss in BW II)	2.5dB max. (-40 to +85°C)
Attenuation(Absolute Value) I)	29.5dB min. at 806.00 to 849.00MHz
Attenuation(Absolute Value) II)	29.5dB min. at 880.00 to 915.00MHz
Attenuation(Absolute Value) III)	30dB min. at 1710.00 to 1785.00MHz
Attenuation(Absolute Value) IV)	30dB min. at 1850.00 to 1910.00MHz
Attenuation(Absolute Value) V)	25dB min. at 1920.00 to 1980.00MHz
Attenuation(Absolute Value) VI)	8.5dB min. at 3300.00 to 3900.00MHz
Attenuation(Absolute Value) VII)	18.5dB min. at 4900.00 to 5900.00MHz
Ripple(max.)	1.5dB
VSWR(max.)	2.3
Characteristic Impedance(Nom.)	50Ω
Power Capacity	1W
Operating Temperature Range	-40°C to 85°C

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




URL: https://www.murata.com/


Last updated :2018/06/22

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=LFB182G60SGHC149} \\$

LFB182G60SGHC149







Frequency Characteristics

Spurious Response

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

