


# LQW2BASR68J00#

"#" indicates a package specification code.



< List of part numbers with package codes >  
 LQW2BASR68J00L , LQW2BASR68J00K , LQW2BASR68J00B

## Shape



## References

Packaging code	Specifications	Minimum quantity
L	φ180mm Embossed taping	2000
K	φ330mm Embossed taping	8000
B	Packing in bulk	500





Mass (Typ.)	
1 piece	0.014g

## Specifications

Inductance	680nH ±5%
Inductance test frequency	25MHz
Rated current (Itemp) (Based on Temperature rise)	190mA
Max. of DC resistance	2.20Ω
Q (min.)	23
Q test frequency	50MHz
Self resonance frequency (min.)	250MHz
Operating temperature range (Self-temperature rise is not included)	-55~125°C
Series	LQW2BAS_00

### Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



**Attention**

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
  - 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.